# **OPSC12 Specification**




10 日 忠 二 1

#### Overview

Decenta OPSC12 is widely used in various scenarios such as education, conference IWB and digital signage.

- 11<sup>th</sup>/10<sup>th</sup> Gen Intel<sup>®</sup> Core<sup>™</sup> i7/i5/i3 Processor.
- 2x DDR4 3200MHz SO-DIMM, Dual channel, Max.64G.
- Support Wi-Fi and Bluetooth.
- Support M.2 SSD, with SATA/PCIe mode.
- Rich interfaces with 3x USB3.0, 3x USB2.0, 1x USB Type-C (optional).
- Supports high resolution of HDMI<sup>®</sup> out 4K@30Hz, DP 4K@60Hz.
- Support for TPM encryption.
- Supports Intel<sup>®</sup> vPro<sup>®\*</sup> technology.

#### I/O Overview




\*Depend on CPU and Network module.

## Specifications

Model			S21-RKLS-OPSC12
CPU			11 <sup>th</sup> /10 <sup>th</sup> Gen Intel <sup>®</sup> Core™ i7/i5/i3 Processor
Chipset			Intel <sup>®</sup> H510
	Туре		2x DDR4 3200MHz SO-DIMM Memory, Dual Channels
Memory	Capacity		Max.64G
Graphic	Controller		Intel <sup>®</sup> UHD Graphics
	Connector		HDMI®/DP
Network		Controller	Realtek 8111H, Co-lay with Intel® i219
	Ethernet	Connector	1Gbe RJ45
		Wi-Fi	1x M.2 E-Key 2230 for WIFI 5/6/6E + BT 5.3
Audio	Audio Controller		Realtek ALC662/897, Co-lay with HS-100B
		SSD	1x M.2 M-Key 2242/2280,Support PCIe & NVMe & SATA mode
Storage	SATA		1
	Front	LAN	1
		USB 3.0	3
		USB 2.0	3
		USB Type-C	1, Optional
		HDMI <sup>®</sup> Out	1 with resolution of 4K@30Hz
I/O		DP	1 with resolution of 4K@60Hz
		Headphone	1
		Mic In	1
		LED	3(P_LED, Power_LED, HDD_LED)
		Power Button	1
		Reset button	1
		Antenna	2
		Kensingdon keyhole	1
	Rear	80Pin Connector	1, with HDMI <sup>®</sup> out of resolution of 4K@60Hz
		DC Jack	1, Reserved
Environment	Temperature	Operating	0°C-45°C
		Storage	-20°C-70°C
	Humidity	Operating	10%~90% non-condensing
		Storage	5%~95% non-condensing
Feature	ТРМ		V2.0 Support, Reserved
	Intel <sup>®</sup> vPro		Optional
	Intel <sup>®</sup> Bios Guard		Y
	Intel®VT-X		Y
	Intel <sup>®</sup> VT-D		Y
Intel®Platform Trust Technology		m Trust Technology	Y
Cooling System			1x Fan & Heatsink
Noise Value			Below 38dB

### Specifications

Model	S21-RKLS-OPSC12
Power	DC 19V
os	Win 10/Win 11
Bios	Insyde BIOS
Dimensions	195mm x 180mm x 30/42**mm
Remark	** 42mm height with handle on Chassis



\*Specifications and information contained in this document are furnished for informational use only, and are subject to change at any time without notice, and should not be construed as a commitment by Decenta.